


MARKSMAN™ 2400

Elite, High Speed Packaging System for Economical Paperboard Wrap Cartons



MARKSMAN™ 2400

Cans

Fourth Generation Can Wrap Machine, Developed with the Japanese Brewery Market in Mind. Focused enhancements support higher throughput speed of 2400 cans per minute, enabling the use of optimized carton sizes, and providing improved performance efficiencies.

Machine Features

Standard

- GPI standard lock
- Dual venturi vacuum generators
- Automatic oil system
- 9 ft (3m) 5000 carton powered magazine
- Market proven segment wheel feeder with optimized geometry

Frame

- Heavy duty welded tubular painted steel frame with corrosion resistant components

Guards

- With full height, clear visibility, sliding guard doors providing easy walk-in access to the machine

Optional

- Powered magazine with capacity for 10,000 cartons
- Dust collection

Specifications

Standard Machine Elevation

41-3/8" +/-2" (1050mm +/-50mm)

Machine Weight

Approx. 16,000lbs (7,300 kg)

Air Requirements

80psi - 16 CFM
(6 bar - 28 m3/h)

Electrical

Japan only

Main Drive Motors

Servo Drive

Changeover

Changeovers for can height/volume are automatically performed by motorized adjustments

Time

10 minutes for can height change

Primary Container Size Ranges

2-piece beverage cans
Diameter: 2.60" (66mm)
Height: 3.58" (91mm) to 6.61" (168mm)

Pack Formats

2x3 only

Pack Styles

Targeted strictly for the Japanese Beer Market, the machine can run two styles of cartons:

TC Wrap, which has gussets on the top corners and chime flaps to interlock with the base of the can.

CC Wrap, which has chime tabs to interlock with the top chime of the can and chime flaps to interlock with the base of the can.


Speed / Pitches

Unpitched product flow allow speeds up to 2,400 cans per minute.

Operates at speeds up to:

Format	Line	Surge
2x3	400ppm	450ppm

Machine Footprint



GPI Rigid Lock Sequence

