


# QUIKFLEX™ 600 G3



**Continuous Motion  
Moderate to High Speed  
Packaging System  
Designed to be as Flexible  
as your Marketplace**

The QuikFlex® 600G3 for fully-enclosed packaging is an industry-proven packaging system for multi-diameter/multi-height Cans, Bottles and PET. This machine features our latest technology and innovation for moderate to high speed requirements on new or existing production lines.

## Machinery Highlights

### No Tool Changeover

Our tool-less changeover technology is quick, simple and repeatable; eliminating time-consuming fine tuning. GPI's IQ Tablet with Changeover Checklist and Video Help enable proven changeover times of 15-30 minutes depending on the change required.

### Functional Design, Easy Access Construction

- Heavy-duty tubular steel frame with corrosion resistant coatings and materials.
- Full height, clear visibility and sliding guard doors provide easy walk-in access to the machine.

### Primary Container Size Ranges

Diameter: 2.1" (53mm) to 3" (76mm)  
Height: 3.5" (89mm) to 9.75" (247mm)

### Machine Features (Standard)

- GPI IQ Tablet - technical & parts manuals, 3D part viewer & changeover checklist
- Runs multi-diameter/height products
- Narrow pack 2x2 53mm capability
- No-tool, quick and repeatable changeovers
- Right or left hand carton loading and controls
- Auto prime and clean-out features
- Walk-in frame
- Text fault display
- 2.5 meter carton magazine
- Ergonomic waist-high carton loading
- Market proven segment wheel feeder
- High volume air assist carton opening
- Wedge metering for smooth product infeed
- Powered overhead

### Machine Features (Optional)

- Additional 3 meter extended carton magazine
- Change parts for additional product and or package formats
- Custom skirting
- Tankless hot melt glue system
- Coder mounting brackets
- Integrated turner divider (with or without reject)
- Auto decaser
- Touchscreen

### Value Added Products and Services:

**Tite-Pak:** Carton handling system for integrated glass-bottle separation and protection.

### Predictive Maintenance Program (PMP):

Let GPI manage your machine maintenance with our market-proven PMP program.

### Specifications

High Speed  
Bottle operation at speeds up to:

Pitch	Line	Surge
6.25"	200	220
12.5"	125	150

Can operation at speeds up to:

Pitch	Line	Surge
6.25"	200	220
12.5"	150	180

(ppm = packs per minute)

### Package Configuration

4,6,8,9,10,12,15,16,18,20 & 24 packs  
Range dependent on primary container diameters

### Frame Dimensions

26' long, 7'-1" wide, 7'-4" high  
(7.92m x 2.16m x 2.23m)

### Machine Weight

Approx. 15,000 lbs (6,850 kg)

### Electrical

Machine: 460 VAC, 60 Hz, 50A  
Gluer: 50A

### Air Requirements

65 PSI-19CFM  
(4.5 Bar-32.3 m3/h)

### Lubrication

Automatic oiler  
Sealed bearings

### Hot Melt

To customer specification

### Machine Footprint

